

Technical Datasheet

Article nr	Fender	Type	Height in mm	inner core	Lenght in mm	Weight kg/mtr	Foam insert
D80							
80.000	D80 LW	straight	80	Ø60	3000	2,9	N/A
80.00	D80 HD	straight	80	Ø40	3000	5	N/A
D100							
100.000	D100 LW	straight	100	Ø80	3000	3,8	N/A
100.00	D100 HD	straight	100	Ø60	3000	6,9	N/A
100.30	D100 SHD	straight	100	Ø40	3000	7,8	N/A
D120							
120.30	D120 SHD	straight	120	Ø60	3000	11,2	N/A
D150							
150.10	D150 MHD	straight	150	D108	3000	11,5	N/A
150.30	D150 SHD	straight	150	D80	3000	16,7	N/A
D190							
190.30	D190 SHD	straight	190	Ø100	3000	27,3	N/A
D250							
250.10	D250 MHD	straight	250	Ø200	3000	23,5	N/A
250.30	D250 SHD	straight	250	Ø190	3000	31,5	N/A
250.40	D250 SHD-S	straight	250	Ø170	3000	37,7	N/A
D300							
300.10	D300 MHD	straight	300	D256	3000	26	LD 45
300.30	D300 SHD	straight	300	D206	3000	45	LD 45
300.40	D300 SHD-S	straight	300	Ø200	4000	55,5	N/A
300.50	D300 SHDS-S	straight	300	Ø150	3000	70	N/A
D350							
350.10	D350 MHD	straight	350	D310	3000	31,7	LD 45
350.20	D350 MHD-S	straight	350	D300	3000	37,6	LD 45
350.40	D350 SHD-S	straight	350	D230	3000	71,5	N/A
D380							
380.40	D380 SHD-S	straight	380	D 250	3000	83	N/A
D450							
450.10	D450 MHD	straight	450	D410	3000	43	LD 45
450.20	D450 MHD-S	straight	450	D390	3000	53	LD 45
C600							
600.00	C600 HD	straight	600	nvt	2000	29	LD 18

other sizes and dimensions on request



**PolyMarine
Service**

FENDER SYSTEMS

Energieweg 46
3133 EC Vlaardingen
The Netherlands

Tel: +31 (0)10 59 179 81
info@polymarineservice.com
www.polymarineservice.com